

Welded pipe nipples
 Carbon steel; DIN2440; welded, or seamless
 Black, Sandblasted
 DIN2999, BSPT, ISO7/1



Size		Threaded Tube DIN2440		Threaded welded nipples have a male thread on one side and a weld end on the other side.					
		O.D.	Wall thickness						
DN	inch	B, mm	S, mm	Length,mm					
6	1/8	10.2	2.0	50	100	150	200	250	300
8	1/4	13.5	2.35	50	100	150	200	250	300
10	3/8	17.2	2.35	50	100	150	200	250	300
15	1/2	21.3	2.65	50	100	150	200	250	300
20	3/4	26.9	2.65	50	100	150	200	250	300
25	1	33.7	3.25	50	100	150	200	250	300
32	1 1/4	42.4	3.25	50	100	150	200	250	300
40	1 1/2	48.3	3.25	50	100	150	200	250	300
50	2	60.3	3.65	50	100	150	200	250	300
65	2 1/2	76.1	3.65	50	100	150	200	250	300
80	3	88.9	4.05	50	100	150	200	250	300
100	4	114.3	4.5	50	100	150	200	250	300
125	5	139.7	4.85	50	100	150	200	250	300
150	6	165.1	4.85	50	100	150	200	250	300

Noted: Other lengths and size available. Grooved end, SQ end and Bevel end available. Contact us for details.